

**PRODUCT DATA SHEET:****INDUSTRIAL GEAR OIL CLP
100/150/220/320/460**

INDUSTRIAL GEAR OIL CLP 100/150/220/320/460 is a range of premium quality heavy duty gear oils, primarily recommended for enclosed gear units working under severe shock operating conditions.

INDUSTRIAL GEAR OIL CLP 100/150/220/320/460 are formulated from carefully selected base stocks and sulphur/phosphorous extreme pressure (EP) additives.

INDUSTRIAL GEAR OIL CLP 100/150/220/320/460 provide excellent protection against high loads, prevent damage on tooth- and friction surfaces. Furthermore the products show excellent protection against rust and oxidation, while the excellent demulsification of the product allows easy water drain off.

INDUSTRIAL GEAR OIL CLP 100/150/220/320/460 are recommended for the lubrication of enclosed spur, helical, bevel and worm gears.

TYPICAL PROPERTIES:						SPECIFICATIONS:
PRODUCT CODE	4370	4372	4374	4376	4378	Exceeds: DIN 51517-3: CLP ISO 12925-1:L-CKC ANSI/AGMA 9005E02 US Steel 224 David Brown S1.53.101(E)
ISO VG	100	150	220	320	460	
DENSITY @ 15°C, kg/m ³	890	894	898	901	907	
VISCOSITY @ 100°C, mm ² /s	11.3	13.6	19.5	22.7	30.5	
FLASH POINT, °C	>210	>200	>200	>200	>235	
POUR POINT, °C	-27	-24	-18	-15	-15	